

Krusemark

CONSTRUCTION 3760 Morrow Ln., Ste. A • Chico, CA 95928 • 916/891-5327 • FAX: 342-4330 • Lic. #490689

October 11, 1991

Thomson & Hendricks
60 Declaration Drive
Chico, CA 95926


ATTN: Dave Dundas

RE: Certification of Compliance for Building Materials
Forest Ranch Elementary School #9006
Chico Unified School District

Dear Dave:

This is to certify, in accordance with the Environmental Protection Agency requirements, that the materials used in the construction of the above referenced project are asbestos-free and are therefore not subject to monitoring for asbestos contamination.

Sincerely,



Randy M. Heuton
General Manager

RMH:lk1

Armstrong Floor Products Asbestos Removal Dates

Technical Information \ Miscellaneous \ Armstrong Floor Products Asbestos Removal Dates
Technical Information \ Technical Bulletins \ Armstrong Floor Products Asbestos Removal Dates

Armstrong World Industries, Inc. no longer manufactures resilient floors or adhesives that contain asbestos.

The information provided below represents the last date for each floor product category that Armstrong produced containing asbestos. Please note, these dates reflect Armstrong's last manufacture, not the products' sale or installation.

COMMERCIAL TILE June, 1981

RESIDENTIAL TILE December, 1982

ADHESIVES (S-89 AND S-90) January, 1983

SHEET VINYL April, 1983

Please be advised that there are federal and, in many states, also state and local regulations which you must consult to determine the procedures required to be followed when removing in-place asbestos-containing materials. Most of these regulations focus on friable materials (those which when dry can be crumbled, pulverized or reduced to powder by hand pressure). In our view, resilient floor coverings are nonfriable and not fairly subject to such regulations. You should be aware that some jurisdictions have regulations which do not take into account the nonfriable nature of the removed material. For this reason, and also because the regulations in your state are always subject to change and sometimes varying interpretations, you should contact the governmental agencies within your jurisdiction to determine which, if any, regulations apply to the removal of resilient floor covering, including the use of RFCI (Resilient Floor Covering Institute) Recommended Work Practices for the Removal of Resilient Floor Coverings.

Unless you are absolutely sure that a previously installed, in-place flooring material does not contain asbestos, you should always assume it does contain asbestos. A copy of the Recommended Work Practices is available at <http://rfci.com/> or by calling 301 340-8580.

If you need additional information on Armstrong floors, contact 1 800 233-2283.