



Bulk Asbestos Point Count Analysis

(NESHAP Final Rule, 40 CFR, Part 61)

Chico Unified School Dist

Client ID:

2921

Leroy Christophersen

Report Number: Date Received:

N001610 05/04/09

2455 Carmichael Drive Chico, CA 95928

Date Analyzed: **Date Printed:**

06/03/09 06/03/09

Job ID/Site: Pleasant Valley Sr., IA Remodel

FALI Job ID:

2921

Sample Preparation and Analysis:

The NESHAP Final Rule does not define the preparation method for multi-layered samples. In order to determine the composite quantity of asbestos, the volume percent of each layer is determined, the asbestos containing layers are analyzed by point counting and the composite quantity of asbestos is calculated. The NESHAP Final Rule can not be applied to matrices that dissolve in refractive index liquid. This includes tar, mastic or adhesive typically found on the back of floor tiles. According to the NESHAP Final Rule, point count data is only necessary when the visual estimate of asbestos is below 10%.

Sample ID	Lab Number	Layer Description	
PVHS01	10864602	Composite of ALL Layers White Drywall Off-White Skimcoat/Joint Compound Paint	
Point Count Results:			
Number of asbestos points counted:		0	

Number of non-empty points:

400

Layer percentage of entire sample:

100

Percent asbestos in layer:

< 1

Asbestos type(s) detected:

Chrysotile

Composite percentage of asbestos in entire sample: <1.00

Comment: Asbestos was detected but no points were counted due to counting criteria. Therefore quantitation deemed to be

PVHS02

10864603

Composite of ALL Layers

White Drywall

Off-White Skimcoat/Joint Compound

Paint

Point Count Results:

Number of asbestos points counted:

1

Number of non-empty points:

400

Layer percentage of entire sample:

100

Percent asbestos in layer:

0.3

Asbestos type(s) detected:

Chrysotile

Composite percentage of asbestos in entire sample:

Comment:

2921

FALL Job ID:



Bulk Asbestos Point Count Analysis

(NESHAP Final Rule, 40 CFR, Part 61)

 Chico Unified School Dist
 Client ID:
 2921

 Leroy Christophersen
 Report Number:
 N001610

 Date Received:
 05/04/09

 2455 Carmichael Drive
 Date Analyzed:
 06/03/09

 Chico, CA 95928
 Date Printed:
 06/03/09

Sample Preparation and Analysis:

Job ID/Site: Pleasant Valley Sr., IA Remodel

The NESHAP Final Rule does not define the preparation method for multi-layered samples. In order to determine the composite quantity of asbestos, the volume percent of each layer is determined, the asbestos containing layers are analyzed by point counting and the composite quantity of asbestos is calculated. The NESHAP Final Rule can not be applied to matrices that dissolve in refractive index liquid. This includes tar, mastic or adhesive typically found on the back of floor tiles. According to the NESHAP Final Rule, point count data is only necessary when the visual estimate of asbestos is below 10%.

Sample ID Lab Number Layer Description



James Flores, Laboratory Supervisor, Hayward Laboratory

Note: Limit of Quantification (LOQ) = 1%. Trace denotes the presence of asbestos below the LOQ. ND = None Detected.

Analytical results and reports are generated by Forensic Analytical at the request of and for the exclusive use of the person or entity (client) named on such report. Results,

Analytical results and reports are generated by Forensic Analytical at the request of and for the exclusive use of the person or entity (client) named on such report. Results, reports or copies of same will not be released by Forensic Analytical to any third party without prior written request from client. This report applies only to the sample(s) tested. Supporting laboratory documentation is available upon request. This report must not be reproduced except in full, unless approved by Forensic Analytical. The client is solely responsible for the use and interpretation of test results and reports requested from Forensic Analytical. This report must not be used by the client to claim product endorsement by NVLAP or any other agency of the U.S. Government. Forensic Analytical is not able to assess the degree of hazard resulting from materials analyzed. Forensic Analytical reserves the right to dispose of all samples after a period of thirty (30) days, according to all state and federal guidelines, unless otherwise specified. All samples were received in acceptable condition unless otherwise noted.